


LTB-8 Rackmount Platform

BRING POWER TO YOUR LAB



PART OF THE
EXFO | FTB Ecosystem



EXFO TFv
Test Function Virtualization



EXFO | MULTILINK

The LTB-8 is a powerful, scalable, eight-slot rackmount platform designed for advanced lab and manufacturing applications.

KEY FEATURES AND BENEFITS

Two configurations: Stand-alone or managed infrastructure for simultaneous multi-user control

Flexible and scalable: Compact 3U solution with high-level module density for in-rack or tabletop applications

Hot swappable: Intelligent module with hot-swap capability, enabling a quick transition from platform to platform, or from rackmount platform to portable platform without powering down

Industrial-grade computer design: Simple, easy-to-use design powered by a quad-core processor with the Microsoft operating system

Out-of-band management: Optimal remote access for maintenance or initial setup using the Intel® Active Management Technology (Intel® AMT)

Connectivity: USB3, LAN, Sync and AMT port for maximum connectivity options

Increased performance and data reliability: RAID 1 mirroring for redundancy and data protection

Automation: Power and flexibility to run automation software and protocol scripts without an external personal computer

Multi-user sharing: Efficient utilization of test resources and minimization of capital expenditures (CAPEX)

RELATED PRODUCTS AND APPLICATIONS



Fiber inspection probe
FIP-400B




100G multiservice test module
FTBx-88200NGE



10G multiservice test modules
FTBx-8870/8880



Multi-user interface
EXFO Multilink




Optical spectrum analyzers
FTBx-5245

EXFO

EXFO'S LTB-8 PLATFORM

The LTB-8 first-in-class platform is a versatile solution addressing numerous transport and datacom applications. Whether in the design lab or during the manufacturing process, the LTB-8 provides users with added versatility and power for today's complex network.



DO MORE!

The Windows 10 operating system allows for a wide choice of third-party applications and supports an extensive range of USB devices.

- › Start faster and multitask
- › Use the Office suite
- › Connect to printers, cameras, keyboards, mice, and more

Bring Your Own Apps



Share your desktop
(e.g., using
TeamViewer)



Antivirus
software



Communicate via
e-mail services
and over-the-top
(OTT) apps



Record and
automate
actions



Share files via
cloud-based
storage

TRANSPORT AND DATACOM MULTISERVICE TEST MODULES



FTBx-88200NGE Power Blazer


- › 40G/100G CFP4 and QSFPx high-speed module
- › Fully loaded, Ethernet testing including 10 GigE, RFC 6349 and EXFO's iSAM for 100G testing
- › OTN multistage, multiplexing testing capabilities with ODU0 and ODUflex support
- › Up to FC16X Fibre Channel true wire-speed traffic generation and monitoring



FTBx8870/8880 Power Blazer

- › Fully loaded, Ethernet testing including 10 GigE dual ports, OTN, RFC 6349 and EXFO's iSAM for 100G testing
- › SONET/SDH, DSn/PDH, ISDN PRI, FTTA, Fibre Channel and packet synchronization

SPECTRAL ANALYSIS IN MANUFACTURING AND LABORATORY ENVIRONMENT



FTBx-5245 optical spectrum analyzers

The FTBx-5245 OSA delivers a full range of spectral analysis capabilities for testing lasers, transmitter optical subassemblies (TOSAs), transmitters, or full optical systems. It supports critical measurements in labs and manufacturing such as:

- › Side mode suppression ratio (SMSR) for DFB lasers and TOSAs
- › Central wavelength measurement
- › Full width half maximum (FWHM) spectral width measurement for Fabry-Perot lasers.
- › Optical power per lane for pluggables like CFPs or QPSP28
- › Insertion loss of passive components such as optical filters
- › Gain and noise figure of erbium doped fiber amplifiers (EDFA)

In addition, the FTBx-5245 offers a complete suite of modes specific to lab and manufacturing applications, such as sources testing (DFB and Fabry-Perot), long-term source characterization (drift mode), EDFA analysis and spectral transmittance analysis.

FIBER CONNECTOR INSPECTION AND CERTIFICATION—THE ESSENTIAL FIRST STEP



Taking the time to properly inspect a fiber-optic cable can prevent a slew of problems down the line—saving you time, money and headaches.

FIP-430B | The first fully automated fiber inspection probe for the field

Housing a unique automatic focus adjustment system, the FIP-430B automates each operation in the connector endface inspection sequence, transforming this critical process into one quick and easy step, which can be performed by technicians of all skill levels.


100%
Automated^a

1-step
process^a

57%
shorter test time^b

THREE MODELS TO FIT YOUR BUDGET

FEATURES	Basic FIP-410B	Semi-Automated FIP-420B	Fully-Automated FIP-430B
Three magnification levels	✓	✓	✓
Image capture	✓	✓	✓
Five-megapixel CMOS capturing device	✓	✓	✓
Automatic fiber image-centering function	X	✓	✓
Automatic focus function	X	X	✓
On-board pass/fail analysis	X	✓	✓
Pass/fail LED indicator	X	✓	✓



ConnectMax2

Read the FIP-400B specification sheet or visit www.EXFO.com/keepthefocus for more information.

Notes

a. Model FIP-430B only.

b. Data sourced from EXFO's case study, with calculation based on typical analysis time.

SOFTWARE TEST TOOLS

These platform-based software testing tools enhance the value of the LTB-8 platform, providing additional monitoring and inspection testing capabilities.

SOFTWARE APPLICATIONS



Providing lightning-fast results in the first step of fiber-link testing, ConnectorMax2 is a powerful platform-based, automated inspection application; it delivers quick pass/fail assessment of connector end faces and is specifically designed to save both time and money in the field and in the lab.

THIRD-PARTY TEST TOOLS

Wireshark

This live-network packet-capture utility makes it possible to look "inside" the packets and obtain data such as transmission time, source, destination, protocol type, etc. Users can then diagnose a problem or root out suspicious behavior.

INTEL® ACTIVE MANAGEMENT TECHNOLOGY (INTEL® AMT)




Remotely manage the platform (out-of-band management) without being dependent on the operating system or the state of the unit. The AMT Web-based application simplifies the out-of-the-box experience and, as an open-source solution, allows programmable remote troubleshooting recovery with extended capabilities and increased effectiveness.

EXFO MULTILINK



EXFO | MULTILINK

The value of connectivity resides in the ability to access your EXFO platform anywhere, using any mainstream Web browser. EXFO Multilink is a multi-user, multichassis and multimodule software application that enables remote control access of each chassis and module through a centralized dashboard.



LTB-8



EXFO | MULTILINK





EXFO TFv
Test Function Virtualization

EXFO TFv

EXFO TFv—Test Function Virtualization is the industry's first suite of defined offerings that focuses on test function virtualization. EXFO TFv offers all the benefits of virtualization through the seamless enablement of test functions on any EXFO test asset, at any time. This suite is ideal for lab managers who are looking to scale their testing requirements to their specific user needs. Under the EXFO TFv umbrella are FTB Anywhere floating licenses and FTB OnDemand time-based software licenses.

Benefits:

- › Maximizes ROI on test equipment expenditures
- › Provides financial flexibility with spending options tailored to CAPEX and/or OPEX
- › Optimizes test-asset investments and ensures the timely availability of required test functionality
- › Enables carriers to gradually increase their test capabilities to match the rollout of new service offerings

FTB Anywhere: floating test licenses

FTB Anywhere allows EXFO's platform users to share floating test licenses and get the required functionality—anywhere, anytime. In short, the customer owns the software licenses and can share them between EXFO's platforms.



FTB OnDemand: time-based software licenses

Part of EXFO TFv, FTB OnDemand allows customers to activate a wide range of test functionalities (e.g., 100G testing) for a specific period of time to match their exact needs. This flexibility is perfect for situations where a test function is only needed for a specific project or for a new service that is still in the early ramp-up stage.

ADAPTED FOR DEDICATED APPLICATIONS. DEDICATED TO HELPING YOU ADAPT.

Thanks to its small format, ultra-powerful processing and highly intuitive interface, the LTB-8 is optimized to enable lab users to carry out dedicated Ethernet and OTN test applications simply and efficiently.

- | | | | | |
|------------------------------|--|--------------------------|------------------------|-----------------|
| 1 Power button | 7 USB 3.0 ports (2) | 13 BNC sync port | 19 USB 3.0 ports (4) | 25 Power supply |
| 2 Power LED | 8 Module status LEDs | 14 RJ45 time-of-day port | 20 Video port (VGA) | |
| 3 Status LED | 9 Module eject button | 15 BNC external clock | 21 Video port (DVI) | |
| 4 Hard disk LED | 10 Module slots (eight available in total) | 16 Dry contact relays | 22 Serial port | |
| 5 System information display | 11 Ethernet ports | 17 Audio port | 23 Hard disk drive bay | |
| 6 Ethernet management port | 12 BNC trigger ports (in and out) | 18 Microphone port | 24 Grounding lug | |



SPECIFICATIONS^a

Mainframe	Quad-core Intel processor/16 GB RAM/Windows 10	
Interfaces	<ul style="list-style-type: none"> › RJ45 LAN 10/100/1000 Mbit/s › USB 3.0 port › DVI and VGA video ports 	<ul style="list-style-type: none"> › Serial RS-232 port › Headset and microphone ports
Storage	256 GB SSD internal memory (flash)	
Power supply	AC input: ~ 100 V – 240 V; 50/60 Hz; 10 – 4.2 A	

GENERAL SPECIFICATIONS


Size (H x W x D) ^b	154 mm × 459 mm × 558 mm (6 1/8 in x 18 1/8 in x 22 in)
Weight	15.5 Kg (34.2 lb)
Temperature	
Operating	0 °C to 40 °C (32 °F to 104 °F)
Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Relative humidity	0 % to 80 % non-condensing

ACCESSORIES

GP-10-101	Ruggedized carrying case	GP-2257	Rackmount brackets (kit of two)
GP-130	GPIB cable (6 feet/2 meters)	GP-2258	USB to GPIB adapter
GP-2016	RJ45 LAN cable (10 feet)	GP-2259	Benchtop feet pads
GP-2256	FTBx module slot blank cover		

Notes

- a. All specifications valid at room temperature.
b. Size only includes feet and not rackmount bracket.

LASER SAFETY

ORDERING INFORMATION

LTB-8-XX-XX-XX

Additional Hard Drive

00 = Without extra hard drive
 RHD = Raid extra hard drive

Inspection Probe Base Tips^a

APC = Includes FIPT-400-U25MA and FIPT-400-SC-APC
 UPC = Includes FIPT-400-U25M and FIPT-400-FC-SC

Inspection Probe Models

00 = Without inspection probe

FP410B = Digital video inspection probe^b
 Triple magnification

FP420B = Analysis digital video inspection probe^b
 Automated pass/fail analysis
 Triple magnification
 Autocentering

FP430B = Automated analysis digital video inspection probe^b
 Automated focus
 Automated pass/fail analysis
 Triple magnification
 Autocentering

Example: LTB-8-RHD-FP-420B-APC

Notes

- a. Available if inspection probe is selected. For more information concerning all available optional tips, please visit EXFO.com/FIPTips.
 b. Includes ConnectorMax2 software.

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. **Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.**

For the most recent version of this spec sheet, please go to www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.