

# EB-MCP-V#-060-####-0808-10



	Unit	Min	Typ	Max
<b>Optical</b>				
Center Wavelength	nm		808	
Wavelength Tolerance	nm		±10	
Output Power	W		60	
Number of Bars	#		2 ~ 60	
Spectral Width (FWHM)	nm			8
Operating Mode	#		CW	
Fast-axis Divergence	Deg		65	
Slow-axis Divergence	Deg		10	
Wavelength Temperature Coefficient	nm/°C		0.28	
<b>Electrical</b>				
Power Conversion Efficiency	%		50	
Slope Efficiency/Bar	W/A	1.1/bar		
Threshold Current	A		25	
Operating Current	A		60	
Operating Voltage/Bar	V			2/bar
<b>Thermal</b>				
Operating Temperature	°C		15 ~ 35	
Bar/Water Velocity/Bar	l/m		0.3~0.5	
Storage Temperature	°C		0~55	
Entrace Maximum Pressure	psi		55	
Water Type	-		DI Water	
Deionized Water Resistivity(DI)	kΩ·cm		200~500	
Pure Water Filter Particles	μm			20

## Remarks

- 1.Explanation of Item Number: EB (Everbright In Short) – MCP (Micro-Channel Cooled Package)–V # (Number of bars per stack) – 060 (QCW Output Power is 60W/bar) – ### (Total Output Power) – 0808 (Center Wavelength ) –10(Wavelength Tolerance)
- 2.Above Data Test at 25°C, Unless otherwise stated.
- 3.Please avoid operation and storage in the condensation enviroment. If exceed operating temperature, the device life-time will be inpacted.
4. Lifetime reduced if exceed nominal output power.

Application Area



R&D



Biomedical



Industrial Pump

Product Features



Cost Effective



High Reliability



High Efficiency



Long Lifetime



SUZHOU EVERBRIGHT PHOTONICS CO., LTD

No.56, Lijiang Road, SND, Suzhou, China

[www.everbrightphotonics.com](http://www.everbrightphotonics.com) [Sales@everbrightphotonics.com](mailto:Sales@everbrightphotonics.com) +86-512-66896988

Notice: Everbright keep improving its products to provide our customers with outstanding quality and reliability. We may change the specification and product description without notice at any time . For complete details, please contact Everbright sales representative.

